

15 W WALL-MOUNT SPEAKER

MC-WSP-315T



100V Power 15W	Frequency Response 70 Hz - 20 kHz
Application Professional audio	Application Professional audio



Description & Key Features

The MC-WSP-315T is a compact wall-mount speaker engineered for professional audio in conference rooms, classrooms and public address zones. Its ABS enclosure and two-way acoustic design provide balanced sound and clear speech intelligibility, while the adjustable bracket supports fast installation and flexible aiming


- Fashionable wall-mount design for professional interiors.
- Suitable for conference rooms and public address applications.
- Adjustable bracket for quick installation and angle control.
- 100V operation for distributed audio systems.
- Two-way design with dedicated tweeter for enhanced clarity.
- Compact black ABS enclosure for durable daily use.



- Fashionable wall mount speaker for conference and PA application.




- Available in 5 inch and 6 inch sizes to suit different venue requirements.



- Quick installation bracket with adjustable angle for flexible mounting.



- Fashionable appearance combined with high quality, balanced sound.



- Switchable operation between 100V and 8ohm for versatile system integration.



- Two-way design featuring a dedicated tweeter for enhanced audio clarity and crisp performance.



TECHNICAL SPECIFICATIONS

GENERAL INFORMATION

Model	MC-WSP-315T
Type	Wall-mount audio system
Application	Commercial PA and sound reinforcement

POWER & PERFORMANCE

Power at 100V	21W
Power at 70V	7.5W
Sensitivity	92 dB +/-1 dB
Frequency Response	70 Hz - 20 kHz

INSTALLATION & BUILD

Enclosure Material	ABS
Installation	Wall mount
Colour	Black

PHYSICAL DETAILS

Speakers	5-inch bass, 0.75-inch tweeter
Package Size	162 x 162 x 243 mm