

HOTEL GUEST ROOM PHONE

MC-APH-R017B/W

Modern Coded Analogue Guest-Room Phone

**Professional Product Overview**

Modern corded analogue landline telephone designed for hotel guest rooms. The unit combines moistureproof construction, an anti-knock handset, DTMF dialling and message-waiting support to provide dependable communication for daily hospitality use.

1-8 Keys

One-touch memory

DTMF

Standard dialling

90-150V DC

MWI support

3 Years

Warranty

Modern guest-room analogue telephone with display, memory keys and message-waiting support

Description & Key Features

The MC-APH-R017B/W is a modern corded analogue landline telephone specifically designed for hotel guest rooms. Its moistureproof body uses durable ABS plastic and a fiberglass PCB to support long service life in hospitality environments.

The device features a high anti-knock handset, DTMF dialling, customisable flash-time options and broad PBX compatibility. It also supports standard 90-150V DC message-waiting light operation for guest notifications.

01 One-Touch Memory Includes 1-8 one-touch memory keys for quick access to hotel services.	02 Moistureproof Design Specially built to remain stable in hotel environments and varying climates.
03 PBX Compatibility Compatible with major PBX systems including Avaya, NEC, Siemens, Philips, Alcatel and Huawei.	04 High Durability Anti-knock handset construction supports frequent guest-room use.
05 Message Waiting Light Supports standard 90-150V DC message-waiting light voltage for guest notifications.	06 Flexible Flash Time 100ms, 300ms and 600ms flash timing options help match technical PBX requirements.

Application Note

Recommended for hotel guest rooms and accommodation projects requiring a modern analogue phone with quick service access, display functionality and reliable PBX compatibility.





Technical Specifications

GENERAL INFORMATION

Model	MC-APH-R017B/W
Type	Hotel Phone
Application	Hotel
Function	One-touch memory
Dial	DTMF

INSTALLATION & BUILD

Material	ABS plastic + fiberglass PCB
Feature	Moistureproof
Handset	High anti-knock resistance
Style	Modern
Warranty	3 years

POWER & PERFORMANCE

Flash Time	100ms, 300ms, 600ms optional; standard 600ms
Message Waiting Light	Standard 90-150V DC
Operating Temperature	-10C to +40C
PBX Compatibility	Avaya, NEC, Siemens, Philips, Alcatel, Huawei

PHYSICAL DETAILS & LOGISTICS

Package Size	23.00 x 10.00 x 25.00 cm
Gross Weight Per Batch	1.5 kg
Packing Quantity	18 PCS / CTN
Transport Package	Paper box

Electrical, Environment & Physical Data

Audio Specifications

Parameter	Specification
Line Inputs	350mV, 10k Ω
Microphone Input	5mV, 600 Ω
Frequency Response	80Hz - 16kHz
THD	<1% at RMS, 1kHz
Signal-to-Noise Ratio	>70dB

Electrical & Environment

Parameter	Specification
Power Supply	DC24V, $\pm$ 20%
Operating Temperature	-20°C to +70°C
Humidity	<95% no condensation

Physical Specifications

Parameter	Specification
Dimensions	256(W) x 149(H) x 52(D) mm
Weight	1.5kg